



## Features

The FreeForm Putty is an excellent water resistant base material for application on walls, which protects the surface and enables excellent finish of paints. The Skim coat plaster material is supplied in powder form and based on high quality hydrophobic polymers and carefully selected graded aggregates. It produces a fine final finish coat. It helps create a durable and stunning final painted wall.

Key features include:

- 

**Lower Dimensional Shrinkage**  
Fewer cracks in concrete
- 

**High Workability**  
Fast completion of project
- 

**Low Requirement of Curing**  
Less supervision required at site
- 

**Thin Layer Application**  
Environmentfriendly
- 

**High Adhesion to Substrate**  
Less peeling off  
High bonding
- 

**Extensively Tested at Factory**  
Quality assurance for you
- 

**No Contamination**  
Better performance
- 

**Water Repellence**  
Moisture ingress & stain protection
- 

**High Consistency of Material**  
Peace of mind

## Application

For most plastered surfaces in interiors and exteriors

## Appearance

Single component premixed plaster powder- ready to use with addition of clean water

## Specifications

<b>Max. Aggregate Size</b>	<b>Compressive Strength</b>
0.5 mm	>7.5 N/mm <sup>2</sup>
<b>Flexure Strength</b>	<b>Bulk Density</b>
>3.5 N/mm <sup>2</sup>	~1200 kg/m <sup>3</sup>
<b>Water Requirement</b>	
~36-40%	
<b>Output/Coverage</b>	
~1.8 kg /mm/m <sup>2</sup>	

## Application Thickness

We recommend to coat the walls in two coats of 1-1.5 mm each.

To achieve an even finish, the material should be skimmed in even thickness. Good finishing saves costs and time in the final finish and it causes less waste.

## Base Surface Preparation

Base surface should be clean and free of dust grease and loose particles or any other material that may restrict adhesion. Any water proofing if required should be completed first.

## Application/Installation Method

Please refer to separate sheet for guidance on application method.

## Curing

The covered surface should be cured with soft water every 6-12 hours from application for the first 2 days.

## Packing

25 kg bag

## Shelf Life

3 months from date of packing before opening. Use within few hours of opening. Store carefully away from dampness and moisture.

## Technical Support

☎ 9374001415 / 0261-2471595

✉ support@freeformbyvyara.in

### Disclaimer

Any recommendations for application techniques are based on experiences. It is advisable to adapt processing techniques and material quantities to the given local conditions and we refer in this context to our general terms of sale and delivery. Hairline crack formation or deformation by shrinkage on principle cannot be excluded with the offered system and thus are not considered as technical defect. Coloured products are exclusively produced from natural raw materials. Thus colour deviations cannot be excluded. The printed colour may deviate from the original colour shade. Test areas are strongly recommended before usage/execution in larger areas.

### Health Precautions

This product contains cement and has an alkaline reaction with moisture/water. Adequately protect hands and eyes. In case of contact with eyes consult doctor immediately.

**Interior, Exterior & Industrial Floors | Wall Finishes | Base Materials | Sealants | DIY**