



## Features

The FormTex finish for walls replicates the exposed RCC looks. This finish can be created on any plastered wall. Offered in many colour options, FormTex lends an understated but definite elegance to the walls and the spaces. FormTex is also a very good option to repair some previous finish that may have gone wrong. Repair or refurbishment in future years is as simple as a paint job.

### Key features include:



Lower Dimensional Shrinkage  
Fewer cracks in concrete



Water Repellence  
Moisture ingress & stain protection



High Adhesion to Substrate  
Less peeling off | High bonding



Low Rebound  
Less wastage in wall material



Low Requirement of Curing  
Less supervision required at site



High Workability  
Fast completion of project



High Consistency of Material  
Peace of mind



High Strength  
High durability | Low maintenance cost

## Application

FormTex can be applied on existing plastered or RCC walls. The application is only carried out by approved

applicators.

## Appearance

FormTex grooves are manually cut out on the walls to the given finish using hand grinders/cutters. Then the specially formulated cement paste is applied, giving an exposed RCC type of look.

## Specifications

Max. Aggregate Size	Compressive Strength
2 mm	>7.5 N/mm <sup>2</sup>
Flexure Strength	Bulk Density
>3 N/mm <sup>2</sup>	~1340 kg/m <sup>3</sup>
Output/Coverage	Water Requirement
~2 kg /mm/m <sup>2</sup>	27.5% (+/- 2.5%)

## Application Thickness

We recommend using the FormTex material in 2 to 3 mm thickness.

## Base Surface Preparation

The base wall surface should ideally be plaster finished, clean and free of undue efflorescence, dust or any other material that may restrict adhesion. Any water proofing if required should be completed first. Any continuous source of water will leave the finish looking imperfect. The base must be consistent, without loose particles and disaggregation.

Use suitable Freeform Primer.

## Application/Installation Method

Please refer to separate sheet for guidance on

application method.

### Curing

Normally no curing is required, unless weather is extremely hot, dry or windy. The finished surface may be lightly sprayed with water soon after completion of work in case of hot and windy climate, to prevent excess drying out.

### Packing

25 kg bag

### Shelf Life

3 months from date of packing before opening. Use within few hours of opening. Store carefully away from dampness and moisture. should be checked.

### Standards

EN: 998-1

### Technical Support

» 9374001415

✉ support@freeformbyvyara.in

#### Disclaimer

Any recommendations for application techniques are based on experiences. It is advisable to adapt processing techniques and material quantities to the given local conditions and we refer in this context to our general terms of sale and delivery. Hairline crack formation or deformation by shrinkage on principle cannot be excluded with the offered system and thus are not considered as technical defect. Coloured products are exclusively produced from natural raw materials. Thus, colour deviations cannot be excluded. The printed colour may deviate from the original colour shade. Test areas are strongly recommended before usage/execution in larger areas.

#### Health Precautions

This product contains cement and has an alkaline reaction with moisture/water. Adequately protect hands and eyes. In case of contact with eyes consult doctor immediately.

**Interior, Exterior & Industrial Floors | Wall Finishes | Tile Adhesives | Base Materials | Sealant | DIY**