



Features

The Terrazzo Grout from FreeForm is available in customised colours to match the terrazzo and cement tile floors. The specially formulated grout is used to fill up the pinholes that may open up after initial grinding in cementitious products that require grinding in an excellent manner.

Key features include:



High Bonding
Better adhesion



High Strength
High durability
Low maintenance cost



Peace of Mind
More value for money



Extensively Tested
Quality assured



No Contamination
Better performance

Application

For cement based floors like Terrazzo floors, cement tiles and other cementitious floors.

Appearance

Single component Cement Powder based- colour as per requirement

Specifications

Max. Aggregate Size

3 mm

Output/Coverage

~2-4 kg/mm/m²

Work Time

Minimum 30 minutes from time of mixing of water

Base Surface Preparation

The surface to be repaired must be clean and without any standing water, and free of any dust or laitance.

Curing

The finished surface may be lightly sprayed with water soon after completion of work in case of hot and windy climate, to prevent excess drying out.

Application Method

The grout mortar should be ideally applied on a rough ground surface. The grout mortar is mixed with recommended quantity of water and a very thin layer of the mixture is repeatedly swept into the pinholes or crevices intended to be filled. The material is left to cure for 2-3 days, after which subsequent grinding can be carried out. If required, the procedure may have to be repeated. Caution— do not leave the grout for a very long period, as it can become very hard and may become difficult to remove from the surface.

Packing

25 kg bag. Smaller pack sizes on request.

Shelf Life

Minimum 3 months from date of packing before opening. Use within few hours of opening. Store carefully away from dampness and moisture.

Technical Support

☎ 9374001415 / 0261-2471595

✉ support@freeformbyvyara.in

Disclaimer

Any recommendations for application techniques are based on experiences. It is advisable to adapt processing techniques and material quantities to the given local conditions and we refer in this context to our general terms of sale and delivery. Hairline crack formation or deformation by shrinkage on principle cannot be excluded with the offered system and thus are not considered as technical defect.

Coloured products are exclusively produced from natural raw materials. Thus colour deviations cannot be excluded. The printed colour may deviate from the original colour shade. Test areas are strongly recommended before usage/execution in larger areas.

Health Precautions

This product contains cement and has an alkaline reaction with moisture/water. Adequately protect hands and eyes. In case of contact with eyes consult doctor immediately.

Interior, Exterior & Industrial Floors | Wall Finishes | Base Materials | Sealants | DIY